

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (canceled)
2. (currently amended) The method of claim ~~[[1]]~~ 20 wherein the ~~defining~~ processing step comprises
  - defining a first traffic class corresponding to the web service;
  - defining at least a second traffic class corresponding to an attribute of the web service;
  - and
  - associating the at least a second traffic class as a child traffic class of the first traffic class in a hierarchical traffic classification scheme.
3. (original) The method of claim 2 wherein the attribute in the second defining step is an operation of the web service.
4. (original) The method of claim 2 wherein the attribute in the second defining step is a binding supported by the web service.
5. (currently amended) The method of claim ~~[[1]]~~ 20 wherein the web services interface definition document is a WSDL document.
6. (currently amended) A method facilitating the classification of web services network traffic, comprising
  - monitoring a data communications path for data flows associated with web services network transactions corresponding to one or more web services traffic;
  - maintaining a tracking list data structure comprising, for each web service detected in

the data flows, a web service identifier corresponding to the web service and a transaction count associated with the web service;

incrementing, responsive to a message indicating a new web services network transaction, a transaction count associated with the web service identified in the message;

presenting, in a user interface, one or more of the web service identifiers and corresponding transaction counts, wherein the user interface allows for selection of one or more web service identifiers; and

configuring, responsive to selection of a web service identifier, a network traffic classification mechanism to identify at least one web service in the data structure based at least on the web service identifier corresponding to the web service the web service corresponding to the web service identifier by creating a traffic class identifier corresponding to the web service; creating at least one matching rule defining an attribute of the web service; associating the at least one matching rule to the traffic class identifier in the traffic classification mechanism.

7. (canceled) .

8. (original) The method of claim 7 wherein the attribute in the second creating step is the web service identifier corresponding to the web service.

9. (original) The method of claim 8 further comprising  
creating at least one additional matching rule defining an attribute of the web service.

10. (original) The method of claim 9 wherein the attribute in the third creating step is a protocol associated with the web service.

11. (original) The method of claim 10 wherein the protocol is a web services protocol.

12. (original) The method of claim 10 wherein the protocol is the SOAP protocol.

13. (original) The method of claim 10 wherein the protocol is the HTTP protocol.
14. (original) The method of claim 6 further comprising  
maintaining a count of the number of data flows corresponding to each web service  
traversing the communications path.
15. (original) The method of claim 6 wherein the web service identifier comprises a host name.
16. (original) The method of claim 6 wherein the web service identifier comprises a host name  
and a uniform resource indicator.
17. (original) The method of claim 6 wherein the configuring step is performed in response to a  
command from an end user.
18. (original) The method of claim 6 wherein the monitoring step comprises  
upon detection of a new data flow,  
parsing at least one packet in the data flow to identify the protocol attributes  
corresponding to the data flow;  
matching the identified protocol attributes to a predetermined set of web  
services protocol attributes to determine whether the data flow is web services web services  
data flow.
19. (original) The method of claim 18 wherein the parsing step comprises parsing the at least  
one packet in the data flow into a flow specification, wherein the flow specification contains at  
least one instance of any one of the following: a protocol family designation, a direction of  
packet flow designation, a protocol type designation, a binding type, a pair of hosts, a pair of  
ports, a pointer to a MIME type, a pointer to an application-specific attribute.

20. (currently amended) A method facilitating the classification of web services network traffic, comprising The method of claim 6 wherein the configuring the network traffic classification mechanism further comprises  
~~monitoring a data communications path for data flows associated with web services network traffic;~~  
~~maintaining a data structure comprising, for each web service detected in the data flows, a web service identifier corresponding to the web service; and~~  
receiving an interface definition document defining the attributes of the ~~the~~ ~~[[a]]~~ web service ~~maintained in the data structure;~~  
processing the interface definition document to identify at least one traffic class corresponding to the web service; and  
configuring a network traffic classification mechanism to identify the at least one traffic class based on at least one attribute obtained from the web services definition document.

21. (original) The method of claim 20 further comprising  
subsequent to the configuring step, processing the latest interface definition document corresponding to the web service to determine whether changes to the configuration of the network traffic classification mechanism are required.

22. (currently amended) An apparatus facilitating the classification of web services network traffic, comprising  
a packet processor operative to  
detect data flows in network traffic traversing a network;  
a traffic classification database operative to  
match data flows against a plurality of traffic classes, wherein each traffic class in the plurality of traffic classes is defined by at least one matching attribute;  
a web services classification module operative to  
identify web services in the data flows traversing the network;  
maintain a tracking data structure comprising, for each web service detected in

the data flows, a web service identifier corresponding to the web service and a count of the number of web services network transactions detected in the data flows traversing the network;  
increment, responsive to a message indicating a new web services network transaction, a transaction count associated with the web service identified in the message;  
present, in a user interface, one or more of the web service identifiers and corresponding transaction counts, wherein the user interface allows for selection of one or more web service identifiers; and

create, responsive to selection of a web service identifier, a traffic class in the traffic classification database for a selected web service in the data structure, wherein at least one matching rule associated with the traffic class includes the web service identifier associated with the web service.

23. (original) The apparatus of claim 22 wherein the web services classification module is further operative to

receive an interface definition document defining the attributes of the selected web service;

process the interface definition document to identify at least one traffic class corresponding to the selected web service; and

create the at least one traffic class in the traffic classification database, wherein at least one matching rule associated with the corresponding traffic class is based on one or more attributes in the interface definition document.

24. (original) The apparatus of claim 23 wherein the at least one traffic class is identified relative to the operations identified in the interface definition document.

25. (original) The apparatus of claim 23 wherein the at least one traffic class is identified relative to the bindings identified in the interface definition document.

26. - 30. (canceled)

31. (new) The apparatus of claim 23 wherein, to process the interface definition document, the web services classification module is further operative to
- define a first traffic class corresponding to the web service;
  - define at least a second traffic class corresponding to an attribute of the web service; and
  - associate the at least a second traffic class as a child traffic class of the first traffic class in a hierarchical traffic classification scheme.
32. (new) The apparatus of claim 31 wherein the attribute in the second defining step is an operation of the web service.
33. (new) The apparatus of claim aim 31 wherein the attribute in the second defining step is a binding supported by the web service.
34. (new) The method of claim 6 wherein the tracking list data structure comprises a hash table including one or more entries, wherein each entry comprises a key value and a transaction count, wherein the key value is generated by applying a hashing function to a host name and URI pair identified in messages initiating web services network transactions.
35. (new) The method of claim 6 further comprising applying one or more bandwidth utilization controls to data flows based on the web services traffic classes associated with the data flows by the traffic classification mechanism.
36. (new) The apparatus of claim 22 wherein the tracking data structure comprises a hash table including one or more entries, wherein each entry comprises a key value and a transaction count, wherein the key value is generated by applying a hashing function to a host name and URI pair identified in messages initiating web services network transactions.